

SAFETY DATA SHEET

Issuing Date 28-Nov-2016

Revision Date 28-Nov-2016

Revision Number 5



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Ipe Oil Hardwood Deck Finish 1 Gal. Natural Wood Oil Based Exterior Water Repelling Stain With UV Protection

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Clear Wood Finish - Sealer

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Deckwise, The Ipe Clip Fastener Company, LLC

Supplier Address 2111 58th Avenue East
Bradenton
Florida
34203
US

Supplier Phone Number Phone: 941 896 9851
Fax: 941 896 9858

Supplier Email info@deckwise.com

Emergency telephone number

Emergency Phone Number 801-569-2426
CHEMTREC 800-424-9300
FAX 801-569-8511

2. HAZARDS IDENTIFICATION

Classification


This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).



Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Flammable liquids	Category 3

GHS Label elements, including precautionary statements

Emergency Overview

Signal word	Danger		
Hazard Statements	Causes skin irritation Causes serious eye irritation May cause respiratory irritation Causes damage to organs through prolonged or repeated exposure Flammable liquid and vapor		
			
Appearance	Brown to dark brown	Physical state	Oil Liquid
			Odor Mild chemical

Precautionary Statements - Prevention

- Wash face, hands and any exposed skin thoroughly after handling
- Wear protective gloves/protective clothing/eye protection/face protection
- Use only outdoors or in a well-ventilated area
- Do not breathe dust/fume/gas/mist/vapors/spray
- Do not eat, drink or smoke when using this product
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Use explosion-proof electrical/ ventilating/ lighting/ equipment
- Keep cool

Precautionary Statements - Response

- Specific treatment (see supplemental first aid instructions on this label)
- Get medical advice/attention if you feel unwell

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention

Skin

If skin irritation occurs: Get medical advice/attention



IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician if you feel unwell

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed
Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

58 % of the mixture consists of ingredient(s) of unknown toxicity

Other information

Toxic to aquatic life with long lasting effects
PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%	Trade Secret
Supplier Trade Secret	Trade Secret	15 - 40	*
Supplier Trade Secret	Trade Secret	5 - 10	*

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice

Show this safety data sheet to the doctor in attendance.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.

Skin contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.



Inhalation	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, (trained personnel should) give oxygen.
Ingestion	Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects	Burning sensation. Coughing and/ or wheezing.
--	---

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, CO₂, water spray or regular foam. Use water spray or fog; do not use straight streams.

Unsuitable extinguishing media

CAUTION: All these products have a very low flash point: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Some may be transported hot.

Uniform Fire Code	Irritant: Liquid Combustible Liquid: II
--------------------------	--

Explosion Data

Sensitivity to Mechanical Impact	None.
---	-------

Sensitivity to Static Discharge	Yes.
--	------

Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. See section 8 for more information. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Other Information Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Environmental precautions

Environmental precautions Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Methods for containment A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Methods for cleaning up Use clean non-sparking tools to collect absorbed material. Dike far ahead of liquid spill for later disposal. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

Incompatible Products Strong acids. Strong oxidizing agents. Strong bases.



8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

The following ingredients are the only ingredients of the product above the cut-off level (or level that contributes to the hazard classification of the mixture) which have an exposure limit applicable in the region for which this safety data sheet is intended or other recommended limit. At this time, the other relevant constituents have no known exposure limits from the sources listed here

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Supplier Trade Secret	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m ³ F TWA: 2.5 mg/m ³ dust (vacated) TWA: 2.5 mg/m ³	
Supplier Trade Secret	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection

Tight sealing safety goggles.

Skin and body protection

Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves. Chemical resistant apron. Antistatic boots.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state

Oil, Liquid



Appearance	Brown to dark brown	Odor	Mild chemical
Color	No information available	Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH	No data available	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	No data available	None known	
Flash Point	40 C / 104 F	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air			
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor pressure	No data available	None known	
Vapor density	No data available	None known	
Specific Gravity	.92	None known	
Water Solubility	Very low solubility	None known	
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octanol/water	4.52	None known	
Autoignition temperature	No data available	None known	
Decomposition temperature	No data available	None known	
Kinematic viscosity	No data available	None known	
Dynamic viscosity	45	None known	
Explosive properties	No data available		
Oxidizing properties	No data available		

Other Information

Softening Point	No data available
VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	



10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components). Prolonged contact may cause redness and irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Supplier Trade Secret	= 13 g/kg (Rat)	> 2 mL/kg (Rabbit)	= 33 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms Erythema (skin redness). May cause redness and tearing of the eyes. Coughing and/ or



wheezing.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	No information available.
Mutagenic Effects	No information available.
Carcinogenicity	Contains no ingredient listed as a carcinogen.
Reproductive toxicity	No information available.
STOT - single exposure	Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from acute exposure. (STOT SE). If this product is a mixture, the classification is not based on toxicology studies for this product, but is based solely on toxicology studies for ingredients found within this product. Detailed substance and/or ingredient information may be provided in other sections of this SDS. Target organs effects listed in this document may result from a single overexposure to this product. Respiratory system.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).
Chronic Toxicity	Possible risk of irreversible effects. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse liver effects.
Target Organ Effects	Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Central Nervous System (CNS). Kidney. Liver. Testes.
Aspiration Hazard	No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)
17,062.00 mg/kg



12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Supplier Trade Secret		48h LC50: 11.5 - 15.8 mg/L (Lepomis macrochirus)	EC50 = 11.1 mg/L 5 min EC50 = 13.4 mg/L 15 min EC50 = 14.3 mg/L 30 min	48h EC50: = 3.68 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

Chemical name	Log Pow
Supplier Trade Secret	3.7

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).
Contaminated Packaging	Dispose of contents/containers in accordance with local regulations.
US EPA Waste Number	D001
California Hazardous Waste Codes	331

14. TRANSPORT INFORMATION

<u>DOT</u>	NOT REGULATED (IF SHIPPED IN NON BULK PACKAGING BY GROUND TRANSPORT)
Proper Shipping Name	NOT REGULATED
Hazard Class	N/A
Emergency Response Guide Number	128

<u>TDG</u>	
UN-No.	UN1263
Proper Shipping Name	PAINT
Hazard Class	3



Packing Group III
Description UN1263, PAINT, III

MEX

UN-No. UN1263
Proper Shipping Name PAINT
Hazard Class 3
Packing Group III
Description UN1263, PAINT, III

ICAO

UN-No. UN1263
Proper Shipping Name PAINT
Hazard Class 3
Packing Group III
Description UN1263, PAINT, III

IATA

UN-No. UN1263
Proper Shipping Name PAINT
Hazard Class 3
Packing Group III
ERG Code 3L
Description UN1263, PAINT, III

IMDG/IMO

UN-No. UN1263
Proper Shipping Name PAINT
Hazard Class 3
Packing Group III
EmS-No. F-E, S-E
Description UN1263, PAINT, III, (40°C C.C.)

RID

UN-No. UN1263
Proper Shipping Name PAINT
Hazard Class 3
Packing Group III
Classification code F1
Description UN1263, PAINT, III

ADR

UN-No. UN1263
Proper Shipping Name PAINT
Hazard Class 3
Packing Group III
Classification code F1
Tunnel restriction code (D/E)
Description UN1263, PAINT, III, (D/E)

ADN

UN-No. UN1263
Proper Shipping Name PAINT
Hazard Class 3
Packing Group III



Classification code F1
 Special Provisions 163, 640E, 650, 367
 Description UN1263, PAINT, III
 Hazard Labels 3
 Limited Quantity 5 L
 Ventilation VE01

15. REGULATORY INFORMATION

International Inventories

TSCA Not determined
 DSL Not determined
 IECSC

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
 Chronic Health Hazard Yes
 Fire Hazard Yes
 Sudden release of pressure hazard No
 Reactive Hazard No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Supplier Trade Secret			X		
Supplier Trade Secret	X				
Supplier Trade Secret	X	X	X		



Supplier Trade Secret	X	X	X		
Supplier Trade Secret	X	X	X	X	X

International Regulations

Mexico

National occupational exposure limits

Chemical name	Carcinogen Status	Exposure Limits
Supplier Trade Secret		Mexico: TWA 100 ppm Mexico: TWA 523 mg/m ³ Mexico: STEL 200 ppm Mexico: STEL 1050 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

Not determined

16. OTHER INFORMATION

NFPA	Health Hazards 2	Flammability 2	Instability 0	Physical and Chemical Hazards - Personal Protection X
HMIS	Health Hazards 2 *	Flammability 2	Physical Hazard 0	

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 28-Nov-2016
Revision Date 28-Nov-2016
Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

